



LIBERA is an open structural system. Roof systems in LIBERA 52 consist of Maxitowers and a LIBERA FL52 grid structure. The actual span can reach 16 metres, to which side wings may be added.

| Dimensions                        | 14 x 12 m          |
|-----------------------------------|--------------------|
| Heights range*                    | from 6 to 9 m      |
| Main truss                        | LIBERA FL52        |
| Towers                            | 4 x Varitower 3-40 |
| Uniformly distributed load UDL ** | 5000 kg ≈          |
| Chain hoists                      | 1000 kg            |
| Total weight                      | 3670 kg            |
| Volume                            | 22 m <sup>3</sup>  |
| Set-up time & number of workers   | 4 hrs / 4 w        |

\* Range suggested according to the dimensions of the roof system.

\*\* Indicative loading data for use in environments without wind. For details and further information, please consult the technical specifications or contact our engineering department or distributors.

For details and further information, please consult the technical specifications or contact our engineering department or distributors.

The examples and data shown on these pages are necessarily indicative owing to the extreme variability of the conditions in which the structures may be assembled. Each installation must be provided with a suitable quantity of ballast, as shown on the product certificates.

This line of structures was created in compliance with European standards. Use of these systems is governed by laws which vary according to the country they are assembled in. They must be put together in compliance with the local regulations in force.



